



## SMT Splice Tape GSM01 Series SMT PET Double Splice Tape 8mm-32mm

Our Product Introduction

for more products please visit us on [smtmachine-spareparts.com](http://smtmachine-spareparts.com)

### Basic Information

- Place of Origin: Shenzhen, china
- Brand Name: GS
- Model Number: GSM0108, GSM0112, GSM0116, GSM0124
- Minimum Order Quantity: 1/box
- Price: USD+negotiable+box
- Packaging Details: 100\*80\*35mm
- Delivery Time: 1-7 days
- Payment Terms: T/T
- Supply Ability: 500+pcs+1-7+days/250+pcs+1-7+days




### Product Specification

- Parts No.1: GSM0108(8mm)
- Dimensions.1(pc): 4.8mm\*40mm
- Parts No.2: GSM0112(12mm)
- Dimensions.2(pc): 6mm\*40mm
- Parts No.3: GSM0116(16mm)
- Dimensions.3(pc): 9.5mm\*40mm
- Parts No.4: GSM0124(24mm)
- Dimensions.4(pc): 16mm\*40mm
- Highlight: 8mm smt splice tape, 32mm smt splice tape, 32mm splice tape 8mm



### More Images



## Product Description

### GSM01 Series SMT PET Double Splice Tape 8mm-32mm

Brand Name : GS

Material: PET

Model Number:

GSM0108, GSM0112,

GSM0116, GSM0124,

Product name: Double Splice Tapes

Application: SMT process

Customization: Support

Lead time: 1-3 Days

DESCRIPTION: GSM01 series Double Splice Tapes are used to join SMT component carrier tapes. Supplied in pre-cut strips of PET tape, use without the splice tool and clip. Each piece has 10 embossed dots on either side to help align with the carrier tape. Three kinds of anti-static, half anti-static and non anti-static.

Part (reel)	Dimensions (pc)	Package(box)
GSM0108 (8mm)	4.8mm x 40mm	500pcs
GSM0112 (12mm)	6mm x 40mm	500pcs
GSM0116 (16mm)	9.5mm x 40mm	500pcs
GSM0124 (24mm)	16mm x 40mm	250pcs



#### Detailed Instructions for Use

1. Cutting the Carrier Tapes: Use the designated cutting tool (GSMTL20/GSMTL30/GSMTL40) to accurately cut the carrier tapes. Precision in cutting ensures a perfect fit and alignment.
2. Preparing the Splice Tape: Remove the release liner of the splice tape to expose the adhesive side. This step is crucial for ensuring a secure bond between the tapes.
3. Aligning the Carrier Tapes: Align the cut carrier tapes (cover tape down) with the placement guide provided.
4. Joining the Carrier Tapes: Place both ends of the joining carrier tapes onto the first strip of the splice tape. Ensure that they are aligned correctly to avoid any misfeeds.
5. Securing the Splice: Fold over the second strip of the splice tape to the underside of the carrier tape and press firmly. This ensures a secure and stable splice.
6. Finalizing the Splice: Remove and discard the clear plastic cover and guide to complete the splice. The tapes are now joined securely and ready for use in the assembly process.

#### Enhancing Manufacturing Efficiency

The GSM01 series Double Splice Tapes are more than just a solution for joining SMT carrier tapes. They represent a significant enhancement in manufacturing efficiency and productivity. By reducing downtime, minimizing machine abrasion, and ensuring continuous operation.



Global Soul Limited



+8613728696610



liyi@gs-smt.com



[smtmachine-spareparts.com](http://smtmachine-spareparts.com)

Room F3B-016, B Block, Hao Yun Lai Bussiness Building, Liutang road , Bao'an District , Shenzhen, China