



Acrylic Adhesive SMT Single Splice Tape GSM06A Series

Our Product Introduction

for more products please visit us on smtmachine-spareparts.com

Basic Information

- Place of Origin: China
- Brand Name: GS
- Model Number: GSM0608/GSM0612/GSM0616/GSM0624
- Minimum Order Quantity: 1 roll
- Price: USD+negotiable+roll
- Packaging Details: 16*36*8mm
- Delivery Time: 1-7 days
- Payment Terms: T/T
- Supply Ability: 1+roll+per days




Product Specification

- Brand Name: GS
- Material: PET
- Model Number: GSM0608/GSM0612/GSM0616/GSM0624
- Product Name: Single Splice Tape Roll
- Application: SMT Process
- Customization: Support
- Highlight: acrylic smt splice tape,
acrylic smt double splice tape,
adhesive smt splice tape



More Images



Product Description

GSM06A Series Acrylic Adhesive SMT Single Splice Tape

GSM06A Single Splice Tape Roll series single splice tape is used for jointing carrier tapes in the SMT process. It is made of one tapes and release paper with superior adhesion. It's suitable for Siemens and Fuji machine.

一、Applications of GSM06A Single Splice Tape Roll

1. Single strips of PET tape on a roll used to join SMT carrier tapes
2. To create a stronger connection, especially on larger carrier tapes, the GSM06A splice tape is used in conjunction with a splice tool and clip. This combination enhances the strength and reliability of the joint.
3. 32mm-88mm available upon request.
4. Accept OEM/EDM.

二、Detailed Instructions for Use

1. Use the Cutting Tool: Begin by accurately cutting the carrier tapes using a splice cutting tool (GSMTL20/GSMTL30/GSMTL40). Precision in this step is crucial to ensure that the joint is secure and that the tapes align correctly.
2. Place Splice Clip on Placement Pins: Place a splice clip (teeth up) on the splice tool's placement pins. This setup prepares the clip for secure attachment to the carrier tapes.
3. Center Carrier Tapes: Center both carrier tapes (cover tape up) on the pins and secure them with the clamps. Ensuring that the tapes are correctly centered is vital for a strong and reliable joint.
4. Crimp the Handle: Crimp the handle of the splice tool to connect the carrier tapes. This step secures the splice clip to the tapes, creating a robust connection.
5. Remove the Release Liner: Remove the release liner of the splice tape to expose the adhesive side. This step ensures that the adhesive is ready to bond with the carrier tapes.
6. Apply Tape Strip: Add a single strip of splice tape to the cover tape and press firmly. This action ensures that the adhesive bonds securely with the carrier tapes, completing the splice.

| Part (reel) | Dimensions (pc) | Package(box) |
|----------------|-----------------|--------------|
| GSM0608 (8mm) | 4.8mm x 45mm | 1000pcs |
| GSM0612 (12mm) | 6mm x 45mm | 1000pcs |
| GSM0616 (16mm) | 9.5mm x 45mm | 1000pcs |
| GSM0624 (24mm) | 16mm x 45mm | 1000pcs |



splice tape black, SMT splice tape for feeders, SMT splice tape compatibility, SMT splice tape usage guide, High-quality SMT splice tape, SMT splice tape for Panasonic, SMT splice tape for Fuji, SMT splice tape adhesive, SMT splice tape performance, SMT splice tape advantages, SMT splice tape for high-speed machines, SMT splice tape durability, SMT splice tape best practices



Global Soul Limited



+8613728696610



liyi@gs-smt.com



smtmachine-spareparts.com

Room F3B-016, B Block, Hao Yun Lai Bussiness Building, Liutang road , Bao'an District , Shenzhen, China