



Dual-Track DIMM Feeder GS-JAT2110 with Siemens PLC Control

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GS
- Model Number: GS-JAT2110
- Minimum Order Quantity: 1/PCS
- Price: USD+negotiable+pcs
- Packaging Details: 900*1500*1650
- Delivery Time: 1-3 days
- Payment Terms: T/T
- Supply Ability: 1+pcs+per days



Product Specification

- Model: GS-JAT2110
- Dimensions (length * Width * Height Company Mm): Please Refer To The Following Drawings
- Weight: 330KG
- Working Voltage: AC 220V
- Air Source Requirements: 0.5-0.7Mpa
- Maximum Power: 1300W
- Feeding Speed: 2.5s/Pcs
- Operation Panel: Siemens Operation Screen
- Control: Siemens Plc
- Thoroughfare: 2 Channels(The Position Can Be Customized In The Left And Right Directions)
- Function: The Color Of The Tested Material Can Be Selected Separately(Default None)
- Adapt To The Material Tray:Please Refer To The Following Drawings
- Material: Compatible With PTH And SMT Materials

for more products please visit us on smtmachine-spareparts.com

Product Description

Dual-Track Dimm Feeder GS-JAT2110 With Air Source Requirements 0.5-0.7Mpa And Control Siemens Plc




Product Specifications

Attribute	Value
Model	GS-JAT2110
Dimensions	Please refer to the following drawings
Weight	330KG
Working voltage	AC 220V
Air source requirements	0.5-0.7Mpa
Maximum power	1300W
Feeding speed	2.5s/Pcs
Operation panel	Siemens operation screen
Control	Siemens plc
Thoroughfare	2 channels (The position can be customized in the left and right directions)
Function	The color of the tested material can be selected separately (Default none)
Adapt to the material tray	Please refer to the following drawings
Material	Compatible with PTH and SMT materials
Condition	New


Product Description

Dimm Cabinet (GS-JAT2110) [Dual Track]

The DIMM tray feeder is a component supply device that installs multiple stacked trays into DIMM slots, arranges them neatly, and sends them out one by one according to the specified time to supply to the plug-in machine.




抛料箱
Material discharge box



轨道靠左, 则抛料箱靠右; 反之轨道靠右, 则抛料箱靠左;
If the track is on the left, the material discharge box is on the right; conversely, if the track is on the right, the material discharge box is on the left

Maximum pallet size
最大托盘尺寸



*托盘尺寸超出此范围, 设备的外形尺寸需要加大。
If the size of the pallet exceeds this range, the external dimensions of the equipment need to be enlarged



物料 (托盘)
Material (Pallet)



成品
Finished product

If there are special material dimensions, you can contact our company for a solution and customize a dedicated feeder.



Global Soul Limited



+8613728696610



liyi@gs-smt.com



smtmachine-spareparts.com

Room F3B-016, B Block, Hao Yun Lai Bussiness Building, Liutang road , Bao'an District , Shenzhen, China