









GS-HQ90 Label Feeder 24V DC 2A Max Current SMT Feeder

Basic Information

Place of Origin: ChinaBrand Name: GSModel Number: GS-HQ90

Minimum Order Quantity:

• Price: USD+negotiable+pcs

1/PCS

Packaging Details: 1000*150*90
Delivery Time: 1-3 days
Payment Terms: T/T

Supply Ability: 1+pcs+per days



Product Specification

Model: GS-HQ90

• Overall Dimensions (length 930*130/72*390mm(There Are Two Widths:

* Width * Height): 130mm And 72mm)

• Weight: 13/9.5(The 130mm Style Weighs 13KG The

72mm Style Weighs 9.5KG)

Working Voltage: DC 24VGas Source Requirements: NoMaximum Current: 2A

Feeding Speed: Adjustable At 35mm/sOperation Panel: 3.5-inch Touchscreen

Feeding Accuracy: +0.3mmCondition: New

Highlight: Label Feeder GS-HQ90, 2A Label Feeder,

DC 24V Label Feeder



2A Maximum Current Label Feeder GS-HQ90 DC 24V Working Voltage

Product Specifications

Attribute	Value
Model	GS-HQ90
Overall dimensions (length × width × height)	930 × 130/72 × 390mm (Two width options: 130mm and 72mm)
Weight	13kg (130mm style) / 9.5kg (72mm style)
Working voltage	DC 24V
Gas source requirements	None required
Maximum current	2A
Feeding speed	Adjustable at 35mm/s
Operation panel	3.5-inch touchscreen
Feeding accuracy	±0.3mm
Condition	New

Product Description

The **GS-HQ90 Label Feeder** is a precision component supply device designed to accurately strip and feed labels from rolls at specified intervals to surface mount technology (SMT) machines.





Tape Specifications

Tape width: Supports tape widths up to ≤85mm

Material spacing: Maintain 2-3mm distance between materials on all sides with 5mm blank areas on both sides

Item density: Limit to 6 items per row (higher density increases potential for abnormalities)

Base paper thickness: Optimal at 0.05mm





+8613728696610



liyi@gs-smt.com



smtmachine-spareparts.com

Room F3B-016, B Block, Hao Yun Lai Bussiness Building, Liutang road, Bao'an District, Shenzhen, China