



GS-SAT2109 Tubular Feeder for Rail Vibration Feeding 10mm-28mm Pipe Width

Our Product Introduction

for more products please visit us on smtmachine-spareparts.com

Basic Information

- Place of Origin: China
- Brand Name: GS
- Model Number: GS-SAT2112
- Minimum Order Quantity: 1/PCS
- Price: USD+negotiable+pcs
- Packaging Details: 1600*90*1250mm
- Delivery Time: 1-3 days
- Payment Terms: T/T
- Supply Ability: 1+pcs+per days



Product Specification

- Model: GS-SAT2109
- Overall Dimensions (length * Width * Height): 1500*90*1140mm
- Weight: 40KG
- Working Voltage: AC 220V
- Gas Source Requirements: 0.5-0.7Mpa
- Maximum Current: 3A
- Feeding Speed: 2s/Pcs
- Operation Panel: 1.54-inch OLED Display Screen
- Pipe Replacement Time: <6S
- Channel: Dual-channel
- Pin Bending Function: Optional Separately(Default None)
- Plastic Surgery Function: Optional Separately(Default None)
- Lifting Function: Optional Separately(Default None)
- Foot Cutting Function: Optional Separately(Default None)



More Images



Product Description

Tubular Feeder GS-SAT2112 for Rail Vibration Feeding

6S Pipe Replacement Adapted to 10mm-28mm Pipe Width

Product Specifications

Attribute	Value
Model	GS-SAT2109
Overall dimensions (L×W×H)	1500×90×1140mm
Weight	40KG
Working voltage	AC 220V
Gas source requirements	0.5-0.7Mpa
Maximum current	3A
Feeding speed	2s/Pcs
Operation panel	1.54-inch OLED display screen
Pipe replacement time	<6S
Channel	Dual-channel
Optional functions	Pin bending, Plastic surgery, Lifting, Foot cutting (available separately)
Material pipe compatibility	Length: 400-600mm Height: 10mm-45mm Width: 10mm-28mm
Condition	New

Product Description

The GS-SAT2109/2112 Tubular Feeder is a rail vibration feeding device designed for efficient supply of tube-mounted electronic components to insertion machines. Utilizing vibration and air blowing technology, it delivers components one by one at precise intervals.

Key Features

- Rapid pipe replacement in under 6 seconds
- Dual-channel operation for increased efficiency
- 1.54-inch OLED display for clear operation monitoring
- Customizable with optional functions as needed
- Wide compatibility with various material pipe dimensions

Custom Solutions Available

For special material dimensions, our engineering team can provide consultation and develop customized feeder solutions to meet your specific requirements.

Product Images









GS-SAT2112(Monorail)

Model	GS-SAT2112	Remarks
Overall dimensions (length * width * height)	1500*76*1140mm	
Weight	35KG	
Working voltage	AC 220V	
Gas source requirements	0.5-0.7Mpa	
Maximum current	2A	
Feeding speed	2s/Pcs	
Operation panel	1.54-inch OLED display screen	
Pipe replacement time	< 6S	
Channel	Single channel	Single or dual channels can be optionally equipped
Pin bending function	Optional separately	Default none
Plastic surgery function	Optional separately	Default none
Lifting function	Optional separately	Default none
Foot cutting function	Optional separately	Default none
Adapt to the length of the material pipe	400-600mm	
Adapt to the height of the material pipe	10mm-45mm	
Adapt to the width of the material pipe	10mm-40mm	

Material pipe style:

(The feeder is customized according to the materials provided by the customer)



Finished product:

(The following are some display pictures)



Global Soul Limited

+8613728696610

liyi@gs-smt.com

smtmachine-sparesparts.com

Room F3B-016, B Block, Hao Yun Lai Bussiness Building, Liutang road , Bao'an District , Shenzhen, China