









# **GS-SHQ2304 Dual-Channel SMT Tube Feeder for IC Components**

#### **Basic Information**

Place of Origin: ChinaBrand Name: GS

Model Number: GS-SHQ2304Minimum Order Quantity: 1 PCS

• Price: USD+negotiable+pcs

Packaging Details: 1250\*80\*400
Delivery Time: 1-7 days
Payment Terms: T/T

Supply Ability: 1+pcs+per days



## **Product Specification**

Model: GS-SHQ2304Overall Dimensions (length 1183\*66\*303

\* Width \* Height):

Weight: 16.5KG
Working Voltage: DC 24V
Gas Source Requirements: 0.4-0.7Mpa

Maximum Current: 2AFeeding Speed: 0.6s/Pcs

• Operation Panel: 0.96-inch TFT Color Screen, 80\*160 Pixels

• Pipe Replacement Time: 5S

 Channel: Dual-channel
 Adapt To The Length Of The Material Pipe: 490-535mm

• Adapt To The Height Of 3.5-5.5mm

The Material Pipe:

• Adapt To The Width Of The 8/11/15mm



## Surface Mount IC Tube Mounting (GS-SHQ2304) [Dual Track]

#### **Product Specifications**

Attribute	Value
Model	GS-SHQ2304
Overall dimensions (L×W×H)	1183×66×303 mm
Weight	16.5 kg
Working voltage	DC 24V
Gas source requirements	0.4-0.7 MPa
Maximum current	2A
Feeding speed	0.6s/Pcs
Operation panel	0.96-inch TFT color screen, 80×160 pixels
Pipe replacement time	58
Channel	Dual-channel
Material pipe length compatibility	490-535mm
Material pipe height compatibility	3.5-5.5mm
Material pipe width compatibility	8/11/15mm
Material length	6.0~12.8mm
Material width	5.0~10.3mm
Material height	1.5~2.5mm

### **Product Description**

The GS-SHQ2304 tubular feeder is a precision electronic component supply device designed for surface mount applications. This dual-track system delivers tube-mounted electronic components to the insertion machine through a combination of vibration and air blowing mechanisms, ensuring accurate and timely component placement.





For components with special dimensions, please contact our technical team for consultation. We can provide customized solutions and exclusive feeder configurations to meet your specific requirements.



