



## GS-RAZ2304 Large Electrolytic Capacitor Feeder for SMT

Our Product Introduction

for more products please visit us on [smtmachine-spareparts.com](http://smtmachine-spareparts.com)

### Basic Information

- Place of Origin: China
- Brand Name: GS
- Model Number: GS-RAZ2304
- Minimum Order Quantity: 1 PCS
- Price: USD+negotiable+pcs
- Packaging Details: 1350\*150\*1200mm
- Delivery Time: 1-7 days
- Payment Terms: T/T
- Supply Ability: 1+pcs+per days



### Product Specification

- Model: GS-RAZ2304
- External Dimensions (length\*Width\*Height): 1152mm\*122.5mm\*900±40mm[For Details, Please Refer To The Size Diagram]
- Weight: 20KG
- Working Voltage: Ac 220V
- Maximum Power: 400W[Direct Vibration: 330W]
- Feeding Speed: 1.5s/Pcs
- Drive Mode: Electric[ Blow Air To Assist In Throwing The Waste Tape]
- Operation Panel: 0.96-inch TFT Color Screen 80\*160 Pixels
- Error In The Length Of The Material Cutting Feet: ±0.1mm
- Applicable To The Hole Spacing Of The Tape: 12.7mm/15mm[ Parts Need To Be Replaced]
- Applicable Material Body Height: ≤47mm
- Applicable Material Dia: ≤0.8mm



### More Images



Product Description

Large Electrolytic Capacitor Feeder GS-RAZ2304 Electronic Component

Product Specifications

Attribute	Value
Model	GS-RAZ2304
External dimensions (L×W×H)	1152mm × 122.5mm × 900±40mm
Weight	20KG
Working voltage	AC 220V
Maximum power	400W (Direct vibration: 330W)
Feeding speed	1.5s/Pcs
Drive mode	Electric (with air assist for waste tape ejection)
Operation panel	0.96-inch TFT color screen (80×160 pixels)
Material cutting length tolerance	±0.1mm
Compatible tape hole spacing	12.7mm/15mm (parts replacement required)
Maximum component height	≤47mm
Maximum pin diameter	≤0.8mm
Maximum pin span	≤30mm
Waste tape cutting function	Standard feature
Cutter durability	≥1 million cycles

Product Description

The GS-RAZ2304 vertical feeder is an electronic component supply device designed for large electrolytic capacitors. It maintains precise intervals while delivering vertically packaged electronic components one by one at specified times. The feeder cuts lead wires and supplies components to the insertion machine with high accuracy.



## Materials



*For components with special dimensions, please contact our technical team for consultation. We can provide customized solutions and exclusive feeder configurations to meet your specific requirements.*



**Global Soul Limited**



+8613728696610



liyi@gs-smt.com



smtmachine-spareparts.com

Room F3B-016, B Block, Hao Yun Lai Bussiness Building, Liutang road , Bao'an District , Shenzhen, China