



Fuji Smart SMT Nozzle Cleaner AHC-R1 Auto Head Cleaner 2A

Basic Information

Place of Origin: Japan Brand Name: fuji

Model Number: 2RGKBM00367**

• Minimum Order Quantity: 1 PCS

Price: USD+negotiable+pcsPackaging Details: 1500*700*800mm

Delivery Time: 1-7 daysPayment Terms: T/T

• Supply Ability: 1+pcs+per days



Product Specification

• TYPE: AHC-R1

• DESIGNA TION: AUTO HEAD CLEANER

DRAWING NUMBER: 2RGKBM0037**
SUPPLY VOLTAGE: AC200V-230V

• FULL LOAD AMP.: 2A

• SHORT-CIRCUIT- 5kA Rms

CURRENT-RATING:

• SHORT-CIRCUT- 14kA

BREAKING CAPACITY:

• FREQ: 50/60Hz

• PHASE: 3

• ENCLOSURE RATING: IP22

• Highlight: Fuji SMT Nozzle Cleaner,

Smart SMT Nozzle Cleaner

Fuji Smart SMT Nozzle Cleaner 2RGKBM00367** DESIGNATION AUTO HEAD CLEANER Full Load Amp. 2A

Product Specifications

Attribute	Value
TYPE	AHC-R1
DESIGNATION	AUTO HEAD CLEANER
DRAWING NUMBER	2RGKBM0037**
SUPPLY VOLTAGE	AC200V-230V
FULL LOAD AMP.	2A
SHORT-CIRCUIT-CURRENT-RATING	5kA rms
SHORT-CIRCUT-BREAKING CAPACITY	14kA
FREQ	50/60Hz
PHASE	3
ENCLOSURE RATING	IP22



Frees operators from nozzle maintenance

Nozzle stations can be set directly after being removed from mounters. The Smart Nozzle Cleaner removes nozzles from stations, and cleans and inspects the nozzles automatically just by pushing the start button.



Accurate inspection

The Smart Nozzle Cleaner checks the conditions of all nozzles and rejects nozzles that do not pass inspection into reject boxes based on the reason for rejection.

Inspection items:

- · Reads 2D codes
- · Checks air flow
- · Checks nozzle sliding movement
- · Checks for nozzle tip damage



Reduces operator work time

Through automation, operator work time can significantly be reduced from 120 to 0.4 seconds per nozzle (excluding inspection time). In a market that often does not have enough staff, this unit greatly contributes to labor saving.

More than 1,000 nozzles can be stored in one unit

Since the Smart Nozzle Cleaner has a large storage capacity, it can be used as a nozzle stocker. Select the right type of operation for your production from the various available operation modes.

Operation modes

- 1. Normal operation Sets nozzles in a nozzle station after cleaning and inspecting the nozzles.
- 2. Exchange operation Exchanges the nozzles in the nozzle station that is set in the Smart Nozzle Cleaner with nozzles in the stocker which have been cleaned and inspected.
- 3. Stocker operation Performs cleaning and inspection for uncleaned nozzles in the stocker.
- 4. Inspection operation Performs inspection on nozzles in a nozzle station set in the Smart Nozzle Cleaner.
- 5. Manual operation Sets the specified types and quantity of nozzles in a nozzle station, or discharges the nozzles onto a tray without setting them in a nozzle station.

FUJI NXT nozzle cleaner, FUJI NXT nozzle cleaner in stock, SMT nozzle cleaning machine, FUJI SMT equipment, automatic nozzle cleaner, pick and place nozzle cleaning, FUJI NXT maintenance, SMT production line, nozzle inspection, electronics manufacturing, SMT automation, FUJI NXT accessories, surface mount technology, SMT machine supplier, Automatic maintenance unit, AutomationEfficiency, Labor-saving, Maintenance, Peripheral equipment, Quality, Smart factory initiative





+8613728696610



liyi@gs-smt.com



e smtmachine-spareparts.com

Room F3B-016, B Block, Hao Yun Lai Bussiness Building, Liutang road, Bao'an District, Shenzhen, China